



# 50 Amp Twist-Lock<sup>®</sup> Devices

## 50A Twist-Lock® Devices

Hubbell's 50 Amp Twist-Lock® Devices feature a heavy-duty design and super-tough nylon housing built for heavy-duty applications and impact resistance, even in the harshest environments. Their rigid construction restricts contact distortion, minimizing the possibility of mating dissimilar devices. The cord grip's offset gripping jaws securely hold the conductors and the cord jacket for excellent strain relief.

- » *Support secure, reliable, superior terminations with Hubbell's box terminals*
- » *Ensure durability with solid, stainless steel shrouds on plugs*
- » *Achieve high heat resistance on receptacles and inlets with thermoset interior components*

Ideal for:



## Ordering Information

### 50A Twist-Lock® Devices

Description	Cord Diameter	Rating	Catalog Number	
Plugs	Nylon housing, thermoplastic polyester interior .830"-1.250" (21.08-31.75)	50A 125V AC	<b>CS6361C</b>	
		50A 250V AC	<b>CS8265C</b>	
		50A 480V AC	<b>CS8465C</b>	
		50A 125/250V AC	<b>CS6365C</b>	
		50A 3Ø 250V AC	<b>CS8365C</b>	
		50A 3Ø 480V AC	<b>CS8165C</b>	
Connector body	Nylon housing, thermoplastic polyester interior .830"-1.250" (21.08-31.75)	50A 125V AC	<b>CS6360C</b>	
		50A 250V AC	<b>CS8264C</b>	
		50A 480V AC	<b>CS8464C</b>	
		50A 125/250V AC	<b>CS6364C</b>	
		50A 3Ø 250V AC	<b>CS8364C</b>	
		50A 3Ø 480V AC	<b>CS8164C</b>	
Flanged inlet	Insulgrip® connector with conduit adapter; capable of accepting metallic or non-metallic conduit fittings ½" NPT size ¾" NPT size 1" NPT size	50A 3Ø 250V AC	<b>CS8364CA05</b> <b>CS8364CA34</b> <b>CS8364CA10</b>	
		Zinc plated steel casing, thermoset interior —	50A 125V AC	<b>CS6377</b>
			50A 250V AC	<b>CS8275</b>
50A 480V AC	<b>CS8475†</b>			
50A 125/250V AC	<b>CS6375</b>			
50A 3Ø 250V AC	<b>CS8375</b>			
Receptacle	Black phenolic —	50A 3Ø 480V AC	<b>CS8175</b>	
		50A 125V AC	<b>CS6370</b>	
		50A 250V AC	<b>CS8269</b>	
		50A 480V AC	<b>CS8469†</b>	
		50A 125/250V AC	<b>CS6369</b>	
		50A 3Ø 250V AC	<b>CS8369</b>	
50A 3Ø 480V AC	<b>CS8169</b>			



Plug



Connector



Flanged Inlet



Receptacle

†Not CSA certified.



## HBL® Series 50A Twist-Lock® Devices

Description	Cord Diameter	Rating			
Plugs	Nylon housing, thermoplastic polyester interior .830"-1.250" (21.08-31.75)	50A 250V DC 50A 600V AC	<b>HBL3763C</b>	<b>HBL3765C</b>	<b>HBL7765C</b>
Connector body	Nylon housing, thermoplastic polyester interior .830"-1.250" (21.08-31.75)	50A 250V DC 50A 600V AC	<b>HBL3762C</b>	<b>HBL3764C</b>	<b>HBL7764C</b>
Flanged inlet	Zinc plated steel casing, thermoset interior	50A 250V DC 50A 600V AC	<b>HBL3777</b>	<b>HBL3775</b>	<b>HBL7958</b>
	Zinc plated steel casing, thermoset interior with lift cover	50A 250V DC 50A 600V AC	<b>HBL3767</b>	<b>HBL3768</b>	<b>HBL7968</b>
Receptacle	Black phenolic	50A 250V DC 50A 600V AC	<b>HBL3771</b>	<b>HBL3769</b>	<b>HBL7379</b>

Female configuration shown.



Plug



Connector



Flanged Inlet with Lift Cover




Receptacle

## Accessories

### Accessories for FS/FD Box Mounting

Description			Catalog Number
Weatherproof receptacle lift cover plates	Corrosion resistant thermoplastic	Gray Yellow	<b>HBL7774WO</b> <b>HBL77CM74WO</b>
	Cast aluminum		<b>HBL7770</b>
Receptacle plates	Cast aluminum; for use with HBL® Series 50A Twist-Lock devices	with lift cover no lift cover	<b>HBL7382*</b> <b>HBL7383</b>
	Stainless steel single gang wallplate		<b>SS750^</b>

\*Not UL Listed "WDL Closed" | \*IP20 suitability



### Receptacle 1/2" Raised Cover

Description	Catalog Number
Galvanized steel; fits 4" square or 2-gang box	<b>HBL50SC^</b>

\*IP20 suitability

### Conduit Adapters

Description	NPT Thread Size	Catalog Number
Thermoplastic housing for use with CS style 50A Twist-Lock® devices	1/2"	<b>CS50CA05</b>
	3/4"	<b>CS50CA34</b>
	1"	<b>CS50CA10</b>



### Weatherproof Boots

Description	Catalog Number	
Seal-Tite® triple seal black elastomeric cover	for plugs when used with cord sets and for connector bodies when used with flanged inlets	<b>HBL7716C†</b>
	for connector bodies when used with cord sets	<b>HBL7717C†</b>

†Not UL Listed



### Inlet Closure Plug

Description	Catalog Number
Black closure plug	<b>HBL4892†</b>

†Not UL Listed



### Replacement Parts

Description	Catalog Number
Cord clamp kit	<b>HBLCSCK</b>



# 50 Amp Twist-Lock® Devices



## Related Products

### Spider® Temporary Power Distribution Boxes

Rating	Type	Qty	Receptacle Rating	Catalog Number
50A 120/240V AC (Maximum)	Straight Blade	6	20A, 125V	<b>TPDS</b>
	Twist-Lock®	1	30A, 250V	
	Twist-Lock® (Inlet)	1	50A, 125/250V	
	Twist-Lock® (Outlet)	1	50A, 125/250V	
50A 120/240V AC (Maximum)	Twist-Lock®	6	20A, 125V	<b>TPDL</b>
	Twist-Lock®	1	30A, 250V	
	Twist-Lock® (Inlet)	1	50A, 125/250V	
	Twist-Lock® (Outlet)	1	50A, 125/250V	



### Temporary Power Cables

Rating	Cable Type	Length (ft)	Catalog Number
50A 125/250V	6/3, 8/1	50	<b>TPC50</b>
		100	<b>TPC100</b>



### Temporary Power Receptacle

Description	Rating	Catalog Number
Pre-wired wall mount receptacle with 3R enclosure and 2' wire leads	50A 125/250V	<b>SR50</b>

## Hubbell Product Literature



**Circuit-Lock®  
Motor  
Disconnects**



**IEC Pin  
and Sleeve  
Devices**



**Watertight  
Wiring Devices**

**HUBBELL®**  
Wiring Device-Kellems

[hubbell.com/wiringdevice-kellems/en](http://hubbell.com/wiringdevice-kellems/en)

